


LETO 11.5

WALL MOUNT LED CYLINDER



Features

- Faceted and Smooth metal reflectors, along with TIR optics provide beam spreads between 10° to 80°.
- Nine drivers selections available to cover wide range of applications.
- Three output options available up to 1500 lumens.
- 5 year warranty.



Finish Options

- White
- Mocha
- Black
- Charcoal
- Silver
- Cerulean
- Firebrick



Technical Information

OUTPUT OPTIONS	700 lm	1000 lm	1500 lm	TM-30					
				CCT	Multiplier	CRI	R _f	R _g	R ₉
Fixture wattage	6.1 W	9.1 W	14.0 W						
Delivered Lumen at 3500K	647 lm	965 lm	1474 lm						
Efficacy	106 lm/W	106 lm/W	105 lm/W						
Center Beam Candlepower (10° Faceted Reflector)	5399 cd	8052 cd	12300 cd						

Integral Driver Example: Fixture LET115-SM-07-25K-F10-NA-WH-WH-PHSD-NA
 Remote Driver Example: Fixture LET115-SM-07-25K-F10-NA-WH-WH-010L-NA
 HRM-LET115-SM-07-25K-010L-NA

Ordering Code

MODEL	TYPE	OUTPUT	CCT	OPTIC	ACCESSORY	BODY FINISH	BAFFLE FINISH
LET115-Leto 11.5	WM-Wall Mount	07-700 lumens (6.1W) ¹ 10-1000 lumens (9.1W) 15-1500 lumens (14.0W)	25K-2500K 27K-2700K 30K-3000K 35K-3500K 40K-4000K 65K-6500K	F10-10 Degree, Faceted F18-18 Degree, Faceted F30-30 Degree, Faceted F45-45 Degree, Faceted F60-60 Degree, Faceted S30-30 Degree, Smooth S45-45 Degree, Smooth S80-80 Degree, Smooth	NA-No Accessory CL-Clear Lens DL-Diffusing Lens HC-Honeycomb Louver SL-Solite Lens	Standard WH-White BK-Black SL-Silver Premium² MA-Mocha CC-Charcoal CR-Cerulean FB-Firebrick	Standard WH-White BK-Black SL-Silver Premium² MA-Mocha CC-Charcoal CR-Cerulean FB-Firebrick
DRIVER ³			DRIVER OPTIONS ⁵				

PHSD-Forward/Reverse Phase, 1% Dimming, 120V Only
 010S-0-10V, 1% Dimming, 120/277V
 0103-0-10V, 1% Dimming, 347V Only
 010L-EldoLED, 0-10V, Linear, 0.1% Dimming, 120/277V
 010G-EldoLED, 0-10V, Log, 0.1% Dimming, 120/277V
 DALI-EldoLED, DALI Protocol 2, DT-6, 0.1% Dimming, 120/277V
 DALI8-EldoLED, DALI Protocol 2, DT-8, 0.1% Dimming, 120/277V
 LUTE-Lutron Hilume Ecodigital, 1% Dimming, 120V/277V
 DMX-EldoLED, DMX, 0.1% Dimming, 120V/277V

NA-None
 EMG-Emergency Driver⁴

1 - 700 lumens is not available with LUTE driver.
 2 - Premium finishes may have extended lead times. Custom RALs are available, please consult Inside Sales with specific request.
 3 - All drivers remote except PHSD/010S driver options.
 4 - Emergency option comes prewired from factory with driver in remote housing. 8W of continuous power provided for a minimum of 90 minutes. Must be installed within 30 feet of luminaire using 18 AWG wire. Not available with 0103, DMX, DALI8 or LUTE Driver.
 5 - AWWNR/CSMB available upon request, contact Senso for details.

CONTACT FACTORY FOR MORE OPTIONS.

Lens & Accessory Options

OPTC-ACC-CL-94MM

Clear Lens

Also available with complete fixture, use ordering code.

-CL



Light Loss Factor: 100%*

OPTC-ACC-DL-94MM

Diffusing Lens

Also available with complete fixture, use ordering code.

-DL



Light Loss Factor: 87%*

OPTC-ACC-HC-94MM

Honeycomb Lens

Also available with complete fixture, use ordering code.

-HC



Light Loss Factor: 45%*

OPTC-ACC-SL-94MM

Solite Lens

Also available with complete fixture, use ordering code.

-SL



Light Loss Factor: 92%*

*Light Loss Factor calculated with 60° faceted reflector.

Optics

RFLC-FXX-94MM

Faceted Reflector

Also available with complete fixture, use ordering code.

-F10/-F18/-F30/-F45/-F60



RFLC-SXX-94MM

Smooth Reflector

Also available with complete fixture, use ordering code.

-S30/-S45/-S60



FXX	Optic
F10	10° Faceted
F18	18° Faceted
F30	30° Faceted
F45	45° Faceted
F60	60° Faceted
S30	30° Smooth
S45	45° Smooth
S60	60° Smooth


Remote Driver Housing

Depending on the options selected in the order code on page 1, a Remote Driver Housing may be required. This will automatically be generated and put on your order as necessary.

REMOTE DRIVER	MODEL	OUTPUT	CCT	DRIVER	DRIVER OPTIONS
HRM-Housing, Remote	LET115-WM-Leto 11.5 Wall Mount	Same as Fixture	Same as Fixture	Same as Fixture	Same as Fixture


Maximum mounting distance to luminaire using 18 AWG wire						
010S	PHSD	010L	010G	DALI DALI8	DMX	LUTE
16'	16'	72'	72'	72'	149'	15'

HRM Single with Externally Mounted Driver




Driver
010L or 010G
010S
010L or 010G or 010S
DALI or LUTE

HRM Single



Driver
PHSD


HRM Double



Driver
DALI8
DMX

EMG Emergency Driver

120 minute EMG operation time.



Driver
EMG

Standard Finishes

BK
Black



WH
White



SL
Silver



Premium Finishes


MA
Mocha




CC
Charcoal



CR
Cerulean






FB
Firebrick



Two Tone Baffle


Inside finish refers to Baffle Finish selection from page 1. Any combination may be used for baffle and body finishes.



TM-30

2500K


COLOR VECTOR GRAPHIC



— Reference Source — Test Source

2700K


COLOR VECTOR GRAPHIC



— Reference Source — Test Source

3000K


COLOR VECTOR GRAPHIC



— Reference Source — Test Source

3500K


COLOR VECTOR GRAPHIC



— Reference Source — Test Source

4000K


COLOR VECTOR GRAPHIC



— Reference Source — Test Source

6500K



COLOR VECTOR GRAPHIC





— Reference Source — Test Source

Photometry



10° Faceted Reflector





30° Smooth Reflector





18° Faceted Reflector





45° Smooth Reflector





30° Faceted Reflector



80° Smooth Reflector



45° Faceted Reflector



60° Faceted Reflector

