

# ARTEMIS 3 W

RECESSED WALL WASHING LED DOWNLIGHT



**Artemis 3 W - Recessed Wall Washing LED Downlight.** Artemis 3 W features a SENSO-designed reflector and a wide range of color temperatures in a high performance yet efficient and compact package. As part of the Artemis family of downlights, it's easy to get a cohesive design regardless of fixture size or style.

## Ordering Code

Fixture	<b>AR3W</b>								
	1	2	3	4	5	6	7	8	9
Driver		<b>AR3W</b>	--			--	--	--	
	1	2	3	4	5	6	7	8	

## Product Specifications

SAMPLE: Fixture **AR3W - TL - A90 - 618 - 25 - 10 - DL - 02 - 08** | Driver **910 - AR3W - TL - STD - 120 - A90 - 07 - 08**

1 - Model	2 - Trim	3 - LED	4 - Optic	5 - CCT	6 - Lumen	7 - Accessory	8 - Trim Color
<b>AR3W</b> · Artemis 3 Wall Wash	<b>FL</b> · Flanged <b>TL</b> · Trimless	<b>A90</b> · Accuracy	<b>618</b> · 18°	<b>25</b> · 2500K <b>27</b> · 2700K <b>30</b> · 3000K <b>35</b> · 3500K <b>40</b> · 4000K <b>65</b> · 6500K	<b>10</b> · 1000 (9.3W) <b>15</b> · 1500 (14.3W) <b>20</b> · 2000 (20.2W) <b>30</b> · 3000 (32.7W)	<b>DL</b> · Diffusing Lens	<b>01</b> · White <b>02</b> · Black <b>08</b> · Silver <b>XX</b> · Custom

9 - Baffle Color	1 - Housing Style	2 - Model	3 - Trim	4 - Driver	Dim Level	Dim Level
<b>01</b> · White <b>02</b> · Black <b>08</b> · Silver <b>XX</b> · Custom	<b>910</b> · Remote <b>915</b> · New Construction <b>920</b> · IC Housing*1 <b>930</b> · Chicago Plenum*1	Same as Fixture	Same as Fixture	<b>STD</b> · Non Dimming <b>LCS</b> · 0 - 10 Volt Protocol <b>DIM</b> · Phase*2/3 <b>ELDOLC</b> · EldoLED 0 - 10 Volt <b>DALI</b> · Dali Protocol	N/A 1% 10% 0.1% 0.1%	<b>LUTES</b> · Hilume Ecodigital <b>LUT2W</b> · 2 Wire for phase*3 <b>LUT5S</b> · 5 Series Eco System <b>DMX</b> · SENSO*4 <b>EMG</b> · Emergency Driver*4/5

5 - Voltage	6 - LED	7 - Lumen	8 - Baffle Color*6
<b>120</b> · 120V <b>277</b> · 277V <b>347</b> · 347V	Same as Fixture	Same as Fixture	Same as Fixture

\*1 Cannot exceed 1500lm  
\*2 Not available in 3000lm  
\*3 Not available in 277V  
\*4 Requires remote housing  
\*5 Specified separately  
\*6 Only needed for Trimless

Project : \_\_\_\_\_  
Quantity : \_\_\_\_\_  
Type : \_\_\_\_\_  
Notes : \_\_\_\_\_

# ARTEMIS 3 W

RECESSED WALL WASHING LED DOWNLIGHT

 **senso**  
by luminii

## Light Engine

- Output:** up to 3000lm
- High Efficacy:** up to 150 lumen/Watt
- Color Options (CCT):** 2500K, 2700K, 3000K, 3500K, 4000K or 6500K
- Color Consistency:** Range within a 3-MacAdam Ellipse
- Color rendering (CRI):** 90 CRI & R9 Value of 50+

## Driver

- Dimming:** 1% dimming standard with 0.1% option
- Ripple:** Industry leading Low ripple
- Efficiency:** Power Factor >0.9  
Efficiency over 85%  
Class 2 output for safety
- Installation:** Small Footprint allows retrofit installations


## Installation

- For new and retrofit installations
- Simple connection between fixture and driver via quick connect
- 18° tilt angle

## Construction / Finish

- Satin powder coated finish
- Custom finishes are available
- Cast Aluminum Trim
- Rated for damp locations
- Made in Canada

## Dimensions





# ARTEMIS 3 W

RECESSED WALL WASHING LED DOWNLIGHT



## Housing Options

### Standard Senso Housing - 910





### Dimension

### Included

Unless specified otherwise, this is provided as standard

- Driver with enclosure**
  - Galvanized steel enclosure
- Installation**
  - Laying on top of ceiling
  - Remote from fixture
  - Hanger bar and mount included

### New Construction - 915





### Dimension

### Included

- Plaster Frame**
  - Galvanized steel construction with cut-out
- Bar hanger**
  - Length: from 14-3/16" to 26"
- Outlet Box**
  - Outlet Box Included

### IC Housing - 920



### Dimension

### Included

- IC Housing**
  - Galvanized steel construction
  - Airtight
  - Includes gasketed junction box
- Plaster Frame**
  - Galvanized steel construction
- Bar hanger**
  - Length: from 14-3/16" to 26"

**Note:** use only with LED modules up to 1500lm

