

SINGLE PHASE SURFACE TRACK

TRACK SYSTEM



standard 120 V with optional data bus system

SPECIFICATIONS

SINGLE PHASE

GENERAL

The 3 conductors (1 live/ 1 neutral/ 1 ground) Senso surface track consists of an extruded aluminum profile which also functions as ground and 2 inserted plastic profiles carrying 2 embedded 12 gauge copper conductors. Any given profile can be easily cut to length on site. It is not necessary to cut back or bend back the conductors. The track has pre-punched holes for mounting every 8" on center.

DATA BUS SYSTEM

enables control for any two wire systems such as 0-10 V, DALI, DMX, Lutron, etc...


FINISH

white (RAL 9010) or black (RAL 9005) powder coated and silver anodized.

Track

Standard Track

4'	8'	12'
○ 235-121	235-241	235-361
● 235-122	235-242	235-362
● 235-123	235-243	235-363



Standard Track with Data bus

4'	8'	12'
○ 238-121	238-241	238-361
● 238-122	238-242	238-362
● 238-123	238-243	238-363

Suspension components

Pendant clip

For pendant mounting with aircraft cables or 3/8" stem. Can be used for electrical connection to the track.


2"	4"
○ 198-00-0001-01	198-00-0002-01
● 198-00-0001-02	198-00-0002-02
● 198-00-0001-03	198-00-0002-03



Clip

(no colour)

8"	12"
198-00-0038-00	198-00-0039-00



T-bar mounting clip

198-00-0004-01 (no colour)



Pendant mounting kit

198-00-0043-00



QUANTITY	PROJECT
NOTE	




SINGLE PHASE SURFACE TRACK

System components

Multiple feed canopy cover



Used to cover an outlet box when using multiple feeds.

- 198-60-0007-01
- 198-60-0007-02
- 198-60-0007-03



Mid feed canopy cover

- 198-00-0026-01
- 198-00-0026-02
- 198-00-0026-03



L-coupler feed

Used to join two sections of track together at a 90° angle. May be used as a feed point.

Standard Track


ground inside ground outside

- 98-525-1 98-526-01
- 98-525-2 98-526-02
- 98-525-3 98-526-03

w/ Data bus

ground inside ground outside

- 98-528-1 98-527-01
- 98-528-2 98-527-02
- 98-528-3 98-527-03



T-coupler feed

Used to join three sections of track in a "T" configuration. May be used as a feed point.

Standard Track

ground right ground left

- 98-529-1 98-530-1
- 98-529-2 98-530-2
- 98-529-3 98-530-3

w/ Data bus

ground right ground left


- 98-532-1 98-531-1
- 98-532-2 98-531-2
- 98-532-3 98-531-3

X-coupler coupler feed

Used to join four sections of track together in an "X" configuration. May be used as a feed point.

Standard Track w/ Data bus

- 98-533-1 98-534-1
- 98-533-2 98-534-2
- 98-533-3 98-534-3




Live end feed (Left)

Used when energizing track from an outlet box or conduit feed.

Standard Track w/ Data bus

- 98-518-1 98-520-1
- 98-518-2 98-520-2
- 98-518-3 98-520-3



Live end feed (Right)

Used when energizing track from an outlet box or conduit feed.


Standard Track w/ Data bus

- 98-519-1 98-521-1
- 98-519-2 98-521-2
- 98-519-3 98-521-3

Floating mid-feed

Standard Track w/ Data bus

- 98-537-1 98-538-1
- 98-537-2 98-538-2
- 98-537-3 98-538-3




I-coupler feed

Used to join two sections of track together in a straight line. May be used as a feed point.

Standard Track w/ Data bus

- 98-523-1 98-524-1
- 98-523-2 98-524-2
- 98-523-3 98-524-3




Flex-coupler feed

Used to join two sections of track together to create angles from 0° to 180°. Can be flexed on horizontal or vertical planes.

Standard Track w/ Data bus

- 98-535-1 98-536-1
- 98-535-2 98-536-2
- N/A N/A



Coupler

Straight

Used to join two sections of track together in a straight line.

Standard Track w/ Data bus

- 98-539-1 98-540-1
- 98-539-2 98-540-2
- 98-539-3 98-540-3



End caps

Used to end any open configuration of track.

- 98-522-1
- 98-522-2
- 98-522-3

